

# Vivitek DH856

高解析高亮度投影機



- 高亮度 4,800 ANSI 流明，可在明亮的會議室中投影
- 15,000:1 超高對比度演示文稿和銳利的文字
- 1080p (1920x1080) 解析度達到最大 WUXGA (1920x1200)
- 6 段 (RGBYCW) 色輪改進和生動的色彩再現
- DLP® Link™ 和 HDMI v.1.4 3D Ready
- 10 瓦音訊揚聲器和音訊輸入輸出連接埠的音訊
- 安靜的操作與低 36dB (Eco 模式下) 雜訊
- 頂級雙面的燈罩為簡單的燈拆卸和安裝
- 多語言 OSD (螢幕顯示) 功能表
- 環保與小於 0.5 w 的電源在待機模式
- 可攜式和羽量級重量只有 3.4 kg
- 防盜安全功能包括：Kensington® 安全插槽、安全欄和電源按鈕鎖定

## Specifications

顯示技術	Single 0.65" DLP Technology by TI
亮度	4,800 Lumens*
解析度	1080P (1920x1080p)
支援最大解析度	WUXGA (1920x1200)@60Hz
對比度	15,000:1
燈泡壽命/類型	3,000/4,000/5,000 Hours (Normal/Eco./Dynamic Eco), 310W/250W
投射比	1.39 - 2.09
螢幕尺寸 (對角線)	25.9" - 324.9"
投影距離	1.2 - 10m
投影鏡頭	F=2.42 - 2.97, f=20.70 - 31.05mm
縮放比例	1.5x
螢幕比例	16:9 Native
仰角	114.9% ±5%
梯形修正	±30 Degree; ±30 Steps
水平頻率	15, 31 - 91.4kHz
垂直頻率	24 - 30Hz, 47 - 120Hz
3D 支援	Yes (DLP® Link™, HDMI 1.4b (Blu-Ray))
揚聲器	10W (Mono)
電腦相容性	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA@60Hz, Mac
影像訊號	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
輸入及輸出連接埠	HDMI v1.4, (x2) VGA-In, Audio-In (Mini-Jack), VGA-Out, USB Power Type A (5V/1.5A) (x2) (For Power Only), Audio-Out (Mini-Jack), RJ45, RS-232, Mini-USB (Service), 12V Trigger
投影方式	Table Top, Ceiling Mount (Front or Rear)
安全鎖	Kensington® Security Slot, Security Bar, Keypad Lock
尺寸(WxDxH)	314 x 213 x 126mm
重量	3.4kg
顏色	Two-Tone: White/Gray
噪音	40dB/36dB (Normal/Eco. Mode)
電源	AC 110-240V, 50/60Hz
功耗	310W (Eco. Mode), 390W (Normal Mode), <0.5W (Standby Mode), <2W (LAN Standby Mode)
標準配件	AC Power Cord, VGA Cable, Remote Control, Documentation Kit
影像訊號	Replacement Lamp, Filter

\*Note: Brightness specifications are in compliance with ISO 21118 standards  
 ©2019 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.

## Photos

