

Multimedia Projector

# Vivitek DX931

高亮度 XGA MHL 投影機



- 超高亮度 4,500 流明及 15,000 :1 高對比度
- Quick auto search filtering to quickly locate input signal source
- 多樣化的輸入及輸出介面: HDMI (x2), VGA-in (2x), VGA-Out, S-Video and Composite Video
- 支援 3D 格式 DLP® Link™ 及 HDMI 1.4b 藍光3D
- 支援 MHL 設備連結

## 規格

顯示技術	Single 0.55" DLP 德州儀器技術
亮度	4,500 流明
解析度	XGA (1024 x 768)
支援最大解析度	WUXGA (1920x1200)@60Hz
對比度	15,000:1
燈泡壽命/類型	2500/3000/3500 小時 (正常/節能/動態節能 模式), 310W/245W
投射比	1.83 - 2.75
螢幕尺寸 (對角線)	21.5" - 269.7"
投影距離	1.2 - 10 m (3.94ft - 2.8ft)
鏡頭	F=2.42 - 2.97, f=20.70 - 31.05mm
變焦	1.5x
比例	4:3 Native
仰角 (垂直)	113.9±5%
梯形修正	±40 Degree; ±40 Steps
Horizontal Frequency	15, 31 - 91.4Hz
Vertical Scan Rate	24 - 30Hz, 47 - 120Hz
3D 支援	Yes (DLP® Link™, HDMI 1.4b (Blu-Ray))
音訊	10W (Mono)
支援影像訊號	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA@60Hz, Mac
支援影像格式	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
輸入及輸出	HDMI v1.4, MHL/HDMI v1.4, VGA-In (x2), S-Video, Composite Video, Audio-In (RCA L/R), Audio-In (Mini-Jack), VGA-Out, USB (Type A for 5V/1.5A Power Only), Audio-Out (Mini-Jack), RJ45, RS-232, Mini-USB (Service), Microphone (Mini-Jack), 12V Trigger
投影方式	桌上,吊掛 (正投或背投)
安全鎖	Kensington® Security Slot, Security Bar, Keypad Lock
體積 (WxDxH)	319 x 216 x 126mm (12.5" x 8.5" x 4.9")
重量	3.17kg (7lbs)
顏色	Dual-Tone: White/Gray
噪聲值	38dB/34dB (Normal/Eco. Mode)
電源	AC 110-240V, 50/60Hz
耗能	320W (Eco. Mode), 410W (Normal Mode), <0.5W (Standby Mode), <2W (LAN Standby Mode)
標準配件	電源線, VGA 連結線, 遙控器, 隨附文件
選購配件	燈泡

©2015 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.



## 產品圖

